Safety Data Sheet (SDS)

According to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and GHS

Section 1: Identification of the Substance/Mixture and the Company/Undertaking

Product Name: Stucco Base Coat Gray Product Code: Stucco Base Coat Gray

Trade Name: Base Coat Gray

Dependable, LLC. Email:

1127 Linda St. info@dependable.us

Rocky River, OH 44116 Phone:

USA 440-605-1020

> For Hazardous Materials [or Dangerous Goods] Incident, Spill, Leak, Fire, **Exposure, or Accident:**

Call CHEMTREC:

+1 703-741-5970 / 1-800-424-9300

CCN839491



GHS Ratings:

Oral Toxicity Acute Tox. 4 Oral>300+<=2000mg/kg

Skin corrosive Destruction of dermal tissue: Exposure < 4 hours

Observation < 14 days, visible necrosis in at least one animal

Eye corrosive 1 Serious eye damage: Irreversible damage 21 days after

exposure, Draize score: Corneal opacity >= 3, Iritis > 1.5

Skin sensitizer 1 Skin sensitizer

Carcinogen 1A Known Human Carcinogen Based on human evidence

GHS Hazards

H302 Harmful if swallowed

H314 Causes severe skin burns and eye damage

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage

H350 May cause cancer

GHS Precautions

P201 Obtain special instructions before use

P202 Do not handle until all safety precautions have been read and understood

P260 Do not breathe dust/fume/gas/mist/vapours/spray P261 Avoid breathing dust/fume/gas/mist/vapours/spray

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product

P272 Contaminated work clothing should not be allowed out of the workplace

SDS for: Stucco Base Coat Gray Page 1 of 8

Printed: 6/24/2024 at 11:20:06AM

Dependable

P280 Wear protective gloves/protective clothing/eye protection/face protection

P281 Use personal protective equipment as required

P310 Immediately call a POISON CENTER or doctor/physician P321 Specific treatment, see supplemental first aid information.

P330 Rinse mouth

P363 Wash contaminated clothing before reuse

P301+P312 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

P302+P352 IF ON SKIN: Wash with soap and water

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing.

Rinse skin with water/shower

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable

for breathing

P305+P351+P338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact

lenses if present and easy to do - continue rinsing

P308+P313 IF exposed or concerned: Get medical advice/attention P333+P313 If skin irritation or a rash occurs: Get medical advice/attention

P405 Store locked up

P501 Dispose of contents/container in accordance with

> local/regional/national/international regulations. Manufacturer/supplier or the competent authority to specify whether disposal requirements apply to contents,

container or both.





Section 3: Composition/Information on Ingredients

Chemical Name	CAS number	Weight Concentration %
Quartz	14808-60-7	30.00% - 60.00%
Portland cement	65997-15-1	10.00% - 30.00%
Limestone	1317-65-3	10.00% - 30.00%
Ethylene-vinyl acetate copolymer	24937-78-8	1.00% - 5.00%

Section 4: First Aid Measures

4.1 Description of First Aid Measures

After Inhalation: Supply fresh air. If required, provide artificial respiration by qualified medical personnel. Keep patient warm. Consult doctor if symptons persist.

After Eye Contact: Remove contact lens if worn. Rinse opened eye for 20 to 30 minutes under running water. If symptoms persist, consult a doctor.

After Skin Contact: Remove all contaminated clothing. Immediately wash affected skin with lukewarm water and soap, rinse thoroughly (20 min.). If skin irritation continues, consult a doctor. After Swallowing: Rinse out mouth and then drink plenty of water. Do not induce vomiting. Call

for medical help immediately.

SDS for: Stucco Base Coat Gray Page 2 of 8

Printed: 6/24/2024 at 11:20:06AM

Notes to Physician: Treat symptomatically

Section 5: Firefighting Measures

Flash Point: 998 C (1,828 F)

LEL: UEL:

5.1 Flammable Limits: Not flammable under normal conditions. Contact with water may cause hvdration, and formation of caustic alkaline material.

5.2 Extinguising Media

Dry Chemical

Alcohol Resistant Foam

Carbon dioxide

Do not use water

5.3 Special Hazards Arising from the Substance of Mixture

Formation of toxic gases is possible during heating or in case of fire.

5.4 Hazardous Combustion Products

Carbon oxides

Sulphur Oxides

Calcium Oxide

Aldehydes

5.5 Advice for Firefighters

Wear self-contained respiratory protective device and other proper protective equipment.

5.6 Fire Damage

Dispose of fire debris and contaminated fire fighting media in accordance with official regulations

Section 6: Accidental Release Measures

6.1 Personal Precautions, Protective Equipment and Emergency Procedures

Avoid dust formation

Do not breathe dust

Avoid contact with skin, eyes and clothing

Remove all non-essential people from the affected area.

Ensure adequate ventilation

Wear protective equipment

6.2 Environmental Precautions: Do not allow to enter sewers/ surface or ground water. Prevent seepage into sewage system, workpits and cellars.

6.3 Methods and Materials for Containment and Cleaning Up:

Ensure adequate ventilation.

Pick up and arrange disposal without creating dust.

Dispose of the collected material according to regulations.

6.4 Reference to Other Sections

For personal protection see Section 8

For disposal information see Section 13.

Section 7: Handling and Storage

7.1 Precautions for Safe Handling

Printed: 6/24/2024 at 11:20:06AM

SDS for: Stucco Base Coat Gray Page 3 of 8 Avoid formation of respirable particles

Do not breath vapours/dust

Do not get in eyes, on skin, or on clothing

Ensure good ventilation/exhaustions at the workplace

Make sure that all applicable workplace limits are observed.

7.2 Conditions for Safe Storage, Including any Incompatibilities

Store in cool, dry conditions in well sealed receptacles

Keep receptacle tightly sealed. Store in dry conditions.

Protect from humidity and water

Storage temperature 10 - 50 °C

Do not store together with oxidizing and acidic materials.

Requirements to be Met by Storerooms and Receptacles: Observe all local and national

regulations for storage of water polluting products.

7.3 Specific End Use(s)

No further relevant information available.

Section 8: Exposure Controls/Personal Protection

8.1 Control Parameters

Ingredients with limit values that require monitoring at the workplace:

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Quartz 14808-60-7	Not Established	0.025 mg/m3 TWA (respirable fraction)	NIOSH: 0.05 mg/m3 TWA (respirable dust)
Portland cement 65997-15-1	15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)	1 mg/m3 TWA (particulate matter containing no asbestos and <1% crystalline silica, respirable fraction)	NIOSH: 10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)
Limestone 1317-65-3	15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)	Not Established	NIOSH: 10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)
Ethylene-vinyl acetate copolymer 24937-78-8	Not Established	Not Established	Not Established

Additional Information: The lists that were valid during the creation were used as a basis.

8.2 General Protective and Hygienic Measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Do not eat, drink, smoke or sniff while working

Keep away foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin

8.3 Personal Protective Equipment:

Eye Protection: Safety glasses with side shields, goggles preferred.

<u>Respiratory Protection:</u> Use suitable respirator protective device in case of insufficient ventilation, required if TLV exceeded. Use suitable respiratory protective device when dust and fumes is formed. NIOSH/MSHA respirator is advised.

Protection of Hands: Protective gloves: to avoid skin problems, the glove material has to be

SDS for: Stucco Base Coat Gray

Page 4 of 8

impermeable and resistant to the product/ the substance/ the preparation. Reccommended glove material: Neoprene, butyl rubber gloves, note: the selection of the suitable gloves does not only depend on the material, but also on the further marks of quality and varies from manufacturer to manufacturer several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application. Protective gloves should be replaced at the first signs of wear. The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Skin and Body Protection: Choose body protection according to the amount and concentration of the dangerous substance at the work place. An eyewash and safety shower stations should be available in the work area.

Section 9: Physical and Chemical Properties

9.1 Information on Basic Physical and Chemical Properties

Vapor Pressure 1.0 mmHg	Boiling Point 2230 °C
Specific Gravity (SG) 3.308	Coating VOC (as 0.00 supplied) lb/gl
Coating VOC (EPA 0.00 calculation) lb/gl	

Section 10: Stability and Reactivity

STABLE

10.1 Reactivity:

Stable under recommeded storage conditions. Interaction with water may cause hydration and formation of alkaline material. No decomposition if stored and applied as directed.

10.2 Chemical Stability:

No decomposition if stored and applied as directed.

10.3 Possibility of Hazardous Reactions:

None known

Hazardous polymerization will not occur.

Section 11: Toxicological Information

Mixture Toxicity

Oral Toxicity LD50: 905mg/kg

Component Toxicity

11.1 Information on Toxicological Effects

Routes of Entry:

No data available

Target Organs:

Eyes Respiratory System Skin

SDS for: Stucco Base Coat Gray Printed: 6/24/2024 at 11:20:06AM Carcinogenicity: The following chemicals comprise 0.1% or more of this mixture and are listed and/or classified as carcinogens or potential carcinogens by NTP, IARC, OSHA (mandatory listing), or ACGIH (optional listing).

Carcinogen Rating CAS Number **Description** % Weight

Quartz 30 to 14808-60-7 Quartz: NIOSH: potential 60% occupational carcinogen

IARC: Human carcinogen

OSHA: listed

Section 12: Ecological Information

12.1 Persistence and Degradability

Product: No further relevant information available

12.2 Bioaccumulative Potential

Product: No further relevant information available

12.3 Mobility in Soil

Product: Distribution among environmental compartments: No further relevant information available.

Additional Ecological Information:

German Hazard Water Class NWG

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

12.4 Results of PBT and vPvB Assessment:

Assessment: This mixture contains no substance considered to be persistent, bioaccumulating nor toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB)

12.5 Other Adverse Effects

Product: No further relevant information available

12.6 Toxicity

Component Ecotoxicity

Section 13: Disposal Considerations

13.1 Waste Treatment Methods

<u>Product:</u> The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with the chemical or used container. Offer surplus and non-recyclable solutions to a licensed disposal company. Send to a licensed waste management company.

Contaminated Packaging: Empty remaining contents. Dispose of as unused product. Do not re-use empty containers.

Section 14: Transport Information

14.1 UN Number:

None - Not Regulated

SDS for: Stucco Base Coat Gray Page 6 of 8

Printed: 6/24/2024 at 11:20:06AM

AgencyProper Shipping NameUN NumberPacking GroupHazard ClassNo data available

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Prop 65 - Chemicals Known to Cause Developmental Toxicity

- None

Prop 65 - Chemicals Known to Cause Cancer:

14808-60-7 Quartz

- U.S. CERCLA/SARA Hazardous Substances and their Reportable Quantities
 - None
- U.S. CERCLA/SARA Section 302 Extremely Hazardous Substances EPCRA RQs
 - None
- U.S. CERCLA/SARA Section 302 Extremely Hazardous Substances TPQs
 - None
- U.S. CERCLA/SARA Section 313 Emission Reporting
 - None
 - None

TSCA (Toxic Substances Control Act)

- None

Country Regulation All Components Listed

USA Inventory - United States - Section 8(b) Inventory (TSCA) Yes
Canada DSL (Canadian Domestic Substance List) Yes

EU Risk Phrases

Safety Phrase

- None

Section 16: Other Information

SDS for: Stucco Base Coat Gray

Page 7 of 8

Printed: 6/24/2024 at 11:20:06AM

We believe the information contained in this SDS is correct, however, because the material may be used under conditions over which we have no control, we give no warranty and assume no responsibility for any damage to person, property or business arising from such use. It is the responsibility of the user to ensure it is properly used. Recipients are advised to confirm in advance of need that the information is current, applicable and suitable to their circumstances. This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Reviewer Revision

Date Prepared: 6/24/2024

SDS for: Stucco Base Coat Gray

Page 8 of 8